The Water Calculator

http://www.thewatercalculator.org.uk/

Congratulations

You are within your target maximum consumption of potable water (110 litres per person per day).

Total water consumption from your calculation **96.34** litres per person per day

This calculator is intended to inform design choices by demonstrating the likely impact of specification changes on total water consumption. Results can only be used to demonstrate compliance with the Code for Sustainable Homes when the calculations have been verified by a suitably qualified Code for Sustainable Homes assessor.

Calculation summary

Installation type	Unit of measure	Capacity / flow rate	Use factor	Fixed use	Litres / person / day
WCs (single flush)	Flush volume (litres)		4.42	0	20.6
WCs (dual flush)	Average effective flushing volume (litres)	4.66			
Taps (excl. kitchen/utility room)	Flow rate (litres / minute)	8	1.58	1.58	14.22
Bath (shower also present)	Capacity to overflow (litres)	156	0.11	0	17.16
Shower (bath also present)	Flow rate (litres / minute)	4.5	4.37	0	19.67
Kitchen/utility room sink taps	Flow rate (litres / minute)	5	0.44	10.36	12.56
Washing machine	Litres / kg dry load	8.17	2.1	0	17.16
Dishwasher	Litres / place setting	1.25	3.6	0	4.5
Waste disposal unit	Litres / use	☐	3.08	0	
Water softener	Litres / person / day	☐	1	0	
Contribution from Grey Water					undefined
Contribution from Rain Water					undefined
				Normalisation factor	∑ × 0.91

water label bma Bathroom Manufacturers Association waterwise

calculator & site development by Seedypea

anglianwater

Product Information

Dual flush WCs		Effective flush volume (litres)	Quantity	Total
	Armitage Shanks – Contour 21 – 1121 – S3078			
		Σ		
		Average Effective flush volume (litres)		

Contribution from Grey Water

Bath, shower, and hand basin usage (l/p/d)		a	
Percentage of used water to be recycled (%)		b	
Greywater available for use (litres/person/day)	0	c	a × (b ÷ 100)
Greywater demand (litres/person/day)		d	
Greywater savings (litres/person/day)	0	e	min {c, d}

Contribution from Rain Water *

Collection area (m^2)		a	
Yield co-efficient and hydraulic efficiency		b	
Rainfall (average mm/year)		c	
Daily rainwater collection (litres)	0	d	(a × b × c) ÷ 365
Percentage collected (%)		e	
Number of occupants	1	f	
Daily rainwater per person (litres)	0	g	(d × e ÷ 100) ÷ f
Rainwater demand (litres/person/day)		h	
Rainwater savings (litres/person/day)	0	i	min {g, h}

* BS 8515 intermediate approach.