Cantero Standard













For a stylish, aesthetically pleasing roof finish, look no further than Cantero Standard slate. The natural minerals, shimmering in the sunlight, make the roof a striking feature and enhance the overall design of your building.

SSQ
EXCLUSIVELY **NATURAL SLATE**

Product information

Product profile

Quarried and hand split exclusively for SSQ in North-West Spain, SSQ Cantero Standard slate has an elegant blue-black colour and strong, deep texture.

SSQ Cantero Standard has achieved excellent results when tested in accordance with EN 12326, in addition to passing SSQ's own rigorous quality control tests, performed at source. It also carries the UKCA marking and is classified as 'W1-T1-S1'.*

Each pallet leaving the quarry is subject to inspection and certification. Independent, random spot checks are also carried out to ensure the best quality.

* Test results are available on request

Appearance

SSQ Cantero Standard roofing slate has a riven texture and a natural unfading deep blue-black colour.

Guarantee

SSQ Cantero Standard roofing slate is covered by 50-year guarantee.**

** Guarantees to be requested within 6 months of the date of completion of the roof.

Minimum headlap for fixing slates with nails or hooks according to BS 5534: 2014+A2:2018 Code of Practice for Slating and Tiling

Moderate exposure (< 56.5 l/m2 per spell)*

Size (mm)	Rafter pitch								
	20°	22.5°	25°	27.5°	30°	35°	40°	45°	80°
500 x 250	–	150	120	100	80	70	60	55	50
450 x 220	–	–	–	–	80	70	60	55	50
400 x 250	–	–	–	–	80	70	60	55	50

Severe exposure (≥ 56.5 l/m2 per spell)*

Size (mm)	Rafter pitch								
	20°	22.5°	25°	27.5°	30°	35°	40°	45°	80°
500 x 250	–	–	–	130	100	90	80	70	65
450 x 220	–	–	–	–	130	120	100	90	65
400 x 250	–	–	–	–	100	90	80	70	65

Size and weight

Size (mm)	Thickness (mm)	Weight per 1000 (kg)
500 x 250	5 - 7	2100
450 x 220	5 - 7	1300
400 x 250	5 - 7	1680

Coverage

Nail fixing method

Size (mm)	Lap (mm)								
	50	65	75	80	90	100	110	115	120
	Number of slates/m²								
500 x 250	17.8	18.4	18.8	19.0	19.5	20.0	20.5	20.8	21.0
450 x 220	21.7	22.6	23.2	23.5	24.2	24.8	25.6	26.0	26.3
400 x 250	22.9	23.9	24.6	25.0	25.8	26.7	27.6	28.1	28.6

(NB: No allowance has been made for wastage*)

Hook fixing method

Size (mm)	Lap (mm)								
	50	65	75	80	90	100	110	115	120
	Number of slates/m²								
500 x 250	17.8	18.4	18.8	19.0	19.5	20.0	20.5	20.8	21.0
450 x 220	21.7	22.6	23.2	23.5	24.2	24.8	25.6	26.0	26.3
400 x 250	22.9	23.9	24.6	25.0	25.8	26.7	27.6	28.1	28.6

(NB: No allowance has been made for wastage*)

* Please refer to the **SSQ Natural Roofing Slate Design and Fixing Guide** for full details (available on www.ssqgroup.com).

The information, both technical and otherwise contained within this guide, is intended to provide illustrations on some of the ways in which SSQ products may be used and should be read in conjunction with all relevant British Standards, Codes of Practice and Health and Safety Legislation. Nothing contained in this brochure nor any advice or recommendation given by or on behalf of SSQ is intended to be relied upon in substitution for an appropriate technical and design appraisal of the specific use to which SSQ products will be put. SSQ will accept no responsibility for any loss or damage howsoever caused that may arise through the reliance being placed on the content of the brochure.

SSQ reserve the right to change designs and specifications without prior notice. All products are subject to our Terms of Business, available on request.
The information and illustrations in this publication were correct at the time of publication.

SSQ Head Office: 301 Elveden Road, Park Royal, London NW10 7SS
T: +44 (0) 20 8961 7725 F: +44 (0) 20 8965 7013
SSQ Northern Irish Office: The YARD Group, 50 Moira Road, Aldergrove, Crumlin, BT29 4JL
T: +44 (0) 79 1239 0505
SSO Spanish Office: C/Academia Dequit No. 11° A, 32300 El Barco de Valdeorras, Orense, Spain
E: info@ssq.co.uk W: www.ssqgroup.com

EXCLUSIVELY **NATURAL SLATE**

® Registered trademark, SSQ Group, November 2024