

Installation Type	Unit of Measure	Capacity/Flow rate (1)	Use Factor (2)	Fixed use (litres/person/day) (3)	Litres/person/day = [(1)x(2)] + (3) (4)
WC (single flush)	Flush Volume (litres)		4.42	0.00	0
WC (dual flush)	Full flush Volume (litres)		1.46	0.00	0
	Part flush Volume (litres)		2.96	0.00	0
WC (multiple fittings)	Average effective flushing Volume (litres)	0.56	4.42	0.00	2.48
Taps (excluding kitchen/utility room taps)	Flow rate (litres/min)	10.00	1.58	1.58	17.38
Bath (where shower also present)	Capacity to overflow(litres)	170.00	0.11	0.00	18.70
Shower (where bath also present)	Flow Rate(litres / minute)	8.70	4.37	0.00	38.02
Bath Only	Capacity to overflow(litres)		0.50	0.00	0
Shower Only	Flow Rate (litres/minute)		5.60	0.00	0
Kitchen/Utility room sink taps	Flow rate (litres/minute)	10.00	0.44	10.36	14.76
Washing Machine	(Litres/kg dry load)	6.00	2.1	0.00	12.60
Dishwasher	(Litres/place setting)	1.25	3.6	0.00	4.5
Waste disposal unit	(Litres/use)	<input type="checkbox"/> Present	3.08	0.00	0
Water Softener	(Litres/person/day)		1.00	0.00	0
(5)	Total Calculated use (litres/person/day) =SUM(column 4)				108.44
(6)	Contribution from greywater (litres/person/day)				0
(7)	Contribution from rainwater (litres/person/day)				0
(8)	Normalisation factor				0.91
(9)	Total internal water consumption = [(5)-(6)-(7)]x(8) (litres/person/day)				98.68
(10)	External water use				5.0
(11)	Total water consumption (Building Regulation 17.K) = (9) + (10) (litres/person/day)				103.7

Installation Type	Make/Model (mandatory)	Litres/Person/Day
WC (multiple fittings)	IDEAL STANDARD I.LIFE A CLOSE COUPLED CISTERN - 4/2.6 L DUAL FLUSH WHITE E247801	2.48
Taps	BRISTAN NIVA BASIN MIXER WITH CLICKER WASTE NVA BAS C	17.38
Baths (shower(s) present)	IDEAL STANDARD I.LIFE 1700MM X 700MM 2TH BATH WHITE T477501	18.70
Showers (bath(s) present)	BRISTAN CRAZE DUAL OUTLET THERMOSTATIC BAR MIXER SHOWER CR22 SHXDIVCTFF C	38.02
Kitchen Taps	UNKNOWN	14.76
Washing Machines	UNKNOWN	17.157
Dishwasher	UNKNOW	4.5

