Specifications Table for 2MXM-N

					2MXM40N2V1B	2MXM50N2V1B	2MXM68N2V1B (Archived)
Dimensions	Unit		Height	mm	550	550	734
			Width	mm	765	765	958
			Depth	mm	285	285	340
Weight	Unit			kg	36	41	60.0
Fan motor	Speed	Cooling	Super low	rpm	500	500	420
		Heating	Super low	rpm	320	500	420
Compressor	Type				Hermetically sealed swing compressor	Hermetically sealed swing compressor	Hermetically sealed swing compressor
Operation range	Cooling	Ambient	Min.	°CDB			-10
			Max.	°CDB			46
Sound pressure level	Cooling		High	dBA	46	48	
			Nom.	dBA			48.0
	Heating		High	dBA	48	50	
			Nom.	dBA			48.0
Refrigerant	Type				R-32	R-32	R-32
	Charge			kg	0.88	1.15	2.00
	GWP				675	675	675.0
Piping connections	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 20m)	0.02 (for piping length exceeding 20m)	0.02 (for piping length exceeding 30m)
	Level difference	IU - OU	Max.	m	15.0	15.0	15.0
		IU - IU	Max.	m	7.5	7.5	7.5

	Total piping length	System	Actual	m	30.0	30.0	50
Standard Accessories	Installation manual				1	1	1
	Screw bag				1	1	1
	Drain plug				1	1	1
	Reducer assembly					1	1
	Drain cap (1)						6
	Drain cap (2)						3
Power supply	Phase				1~	1~	1~
	Frequency			Hz	50	50	50
	Voltage			V	**220-230-240**	**220-230-240**	220-240
Notes					(1) - For one room	(1) - For one room	(1) - For one room
					(2) - See separate drawing for operation range	(2) - See separate drawing for operation range	(2) - See separate drawing for operation range
					(3) - See separate drawing for electrical data	(3) - See separate drawing for electrical data	(3) - See separate drawing for electrical data
					(4) - Contains fluorinated greenhouse gases	(4) - Contains fluorinated greenhouse gases	(4) - Contains fluorinated greenhouse gases