TECHNICAL | SPECIFICATION

Complete range of sizes available in the *Titan* series.

New **Titan** Series				
Dimensions in metres	**TN104**	**TN124**	**TN154**	**TN184**
External length	10.01	12.41	14.81	18.41
External width	4.19	4.19	4.19	4.19
External height*	2.98	2.98	2.98	2.98
Internal length (m)	9.56	11.96	14.36	17.96
Internal width (m)	3.75	3.75	3.75	3.75
Ceiling height (m)	2.50	2.50	2.50	2.50
Height from lorry platform	2.91	2.91	2.91	2.91
Leg centres (length)	7.20	7.20	7.20	9.60
Leg centres (width)	4.03	4.03	4.03	4.03
Foundation to floor level	0.31	0.31	0.31	0.31
Floor area (m^2)	35.80	44.79	53.78	67.26
Minimum sling leg length	6.00	6.00	6.00	7.50
Minimum hook height	7.30	7.30	7.30	8.30
Empty module weight (kg)**	4706	5658	6541	7974
Maximum handling weight (kg)***	10000	10000	10000	10000
Two-storey building dimensions (m)				
External height*	5.95	5.95	5.95	5.95
Ground floor level to first floor level*	2.97	2.97	2.97	2.97
All other dimensions are as detailed for a single-storey building.				

* *Lodastrut* legs fully retracted.
** When handling by crane or the *Lodastrut* leg system
*** With four *Lodastrut* legs fitted.

