

SECTION C150 C200 C250 C300 C400 CLEAT 75 X 50 X 3 75 X 65 X 3 75 X 75 X 6 75 X 75 X 6 75 X 75 X 6 ANCHOR 2 X M16 X110 2 X M16 X110 2 X M16 X110 2 X M16 X110 2 X M16 X110 (Per Column - For back to back - double quantity) FOOTING DETAIL SEE FOUNDATION PLAN FOR TYPE AND SIZE WIDTH BxB (SQ.) DETAIL A 1	R1 & R2 1 x CAPITAL STEEL HAUNCH BRACKET 16 - M16 4.6/S PER BRACKET C1 & C2 DETAIL B 1	R1 & R2 2 x CAPITAL STEEL APEX PLATE FOR DOUBLE CHANNEL 1 x CAPITAL STEEL APEX PLATE FOR SINGLE CHANNEL 8 - M16 4.6/S PER CONNECTION DETAIL C 1	Mullion top angle 4-M12 4.6/S Rafter End Wall Girt Mullion 140 DETAIL D 1	C3 REFER TO DETAIL A FOR CLEAT SIZE AND SLEEVE ANCHOR FOOTING DEPTH D WIDTH BxB (SQ.) DETAIL E 1					
BASE CONNECTION	UBC - 140	HAUNCH CONNECTION	HB400-140	APEX CONNECTION	AB400-140	MULLION CONNECTION	MCT-140	END MULLION CONNECTION	MCB
R2 C4 C4 BOLT TO APEX USING 4 FRAMING BOLTS IF CENTRED BOLT TO RAFTER USING 4 FRAMING BOLTS IF OFFSET DETAIL F 1	C4 REFER TO DETAIL A FOR CLEAT SIZE AND SLEEVE ANCHOR FOOTING DEPTH D WIDTH BxB (SQ.) DETAIL G 1	Eave Purlin Side Wall Girts Side R/Door Mullion Type 1 Side R/Door Mullion Type 2 Anchored to base via base cleats and sleeve anchors Opening Side Wall Girt DETAIL H 1 Side Roller Door columns are connected to the next girt above the opening, Type 1, or to the eave purlin, Type 2.	GP Bracket 4 - 12 x 20 Teks Per connection Rollerdoor Header Rollerdoor Post DETAIL I 1	15% OVERLAP P1, G1 & G2 C1, R1, C3 & M1 4-No14x20 TEKS PER FIXING POINT 4-No14x20 TEKS PER SUPPORT, TYP. FLY BRACE SHALL BE LOCATED AT 3000 CENTRES MAX ON COLUMNS AND RAFTERS DETAIL J 1					
END ROLLER DOOR COLUMN CONNECTION	ERCT	END ROLLERDOOR COLUMN BASE	RCB150-61	SIDE ROLLERDOOR COLUMN	SRDJ	Rollerdoor Header	RDH01	PURLIN/GIRT CONNECTION	PGC-140
End Rafter Additional End Wall Girt added Door header to required height End Column Existing End Wall Girts Door Frame Anchored to base via cleats and sleeve anchors DETAIL K 1	End Column/Mullion. End Wall Girt 4 Frame Screws per connection DETAIL L 1	Column Rafter Roof Purlin Tophat or Zed Diagonal Bracing with 2 - 12 x 20 teks per connection to column or rafter. Must wrap over purlin or girt. Wall Girt Tophat or Zed Not required in all buildings DETAIL M 1	(Roof & Wall) Intermediate Fixing Schedule (Roof Only) Eave Fixing Schedule (Roof Only) End Lap Fixing Schedule DETAIL N 1	(Roof & Wall) Intermediate Fixing Schedule (Roof Only) Eave Fixing Schedule (Roof Only) End Lap Fixing Schedule DETAIL O 1					
PA DOOR JAMBS-VERTICALLY CLAD END WALL	PADV	End Wall Girt Connection	EG140	Diagonal Bracing	DB01	AS35 Composite Panel	AS35CP	AS35 Composite Panel	AS35CP

DETERMINED
PLAN

SHDC
Planning & Development
22 MAY 2009
Ref: 0363/09

Capital Steel Buildings

Web: www.capitalsteelbuildings.co.uk
Email: info@capitalsteelbuildings.co.uk

Supplied By: Airblast Ltd

Phone 01778 560650 Fax 01778 560724
King Street Industrial Estate, Langtoft, Peterborough, PE6 9NF,

Customer: MARK SCOTTNEY

XXX