SITE SURFACES & BOUNDARY TREATMENTS

SURFACE TREATMENT

- TARMAC DRIVES & ROADS
- GRAVEL
- GRASS - (Note only front Gardens to be Turfed unless otherwise stated).
- COBBLES SET IN CONCRETE
- 600mm SQUARE GREY PAVING SLAB LOCATED AT END OF PARKING SPACE (GRAVEL OR TARMAC) HOUSE NUMBER PAINTED ON

PRIVATE FOOTPATH TREATMENT F6

- LL -LEVEL LANDING TO LEVEL THRESHOLD 1.2m WIDE x 0.9m DEEP (MIN. SIZE)
- S - STEP - MAX RISER 200mm
- F9 -900mm WIDE FOOTPATH IN PAVING SLABS
- F6 -600mm WIDE FOOTPATH IN PAVING SLABS
- RAMP - TO BE NO GREATER THAN 1:15 GRADIENT

BOUNDARY TREATMENT

- CB18 - CLOSE BOARD FENCE 1800mm HIGH
- PAN18 -TIMBER PANEL FENCE 1800mm HIGH
- PR12 - TIMBER POST & RAIL 1200mm HIGH
- PG -PERSONNEL GATE - 1800mm HIGH FITTED WITH SHOOT BOLT.TIMBER GATES TO BE USED (UNLESS STATED OTHERWISE)
- R9+PG - RAILINGS 900mm HIGH (see Detail) + PG OF SAME STYLE/MATERIAL.

N W E S

Existing Dwelling (281) Existing Garage (280) Existing Dwelling (279) (278) (277) (301)

Existing Shrubs / Bushes — DRAIN — Proposed Foul Pumping Station — Public Foot / Cycle — Public Foot / Cycle — TARMAC — Tarmac — Public Foot / Cycle — STRATEGIC FOOT / CYCLE — Public Foot / Cycle — Public Foot / Cycle — Public Foot / Cycle