NOTES

1. Contractors must check all dimensions on site. Only figured dimensions are to be worked from. Discrepancies must be reported to the Architect or Engineer before proceeding. © This drawing is copyright.

2. Until technical approval has been obtained from the relevant authorities, all drawings are issued as preliminary and not for construction. Should the Contractor commence site work prior to approval being given it is entirely at his own risk.

SAFETY, HEALTH AND ENVIRONMENTAL

In addition to the hazards, risks normally associated with the type of work detailed on this drawing, note the following significant risks and information.

Construction:

1. Groundwater control may be required for excavations in excess of 2m or as deemed necessary.

For information relating to end use, maintenance, demolition, see the health and safety file.

It is assumed that all works will be carried out by a competent Contractor, where appropriate, to an approved method statement.

KEY

- Blacktop carriageway construction
- Blacktop footway construction
- Block paved single driveway construction
- Block paved single driveway construction in contrasting colour
- Block paved shared driveway construction
- Block paved shared driveway construction in contrasting colour
- Block paved driveway in constrasting colour Heavy duty construction
- Vehicular crossover
- Tactile paving
- 900mm wide path - 450 x 450mm paving slabs
- 600mm wide path - 600 x 600mm paving slabs
- 1.8m x 1.8m patio - 600 x 600mm paving slabs
- 1 STP — Steps - indicating number required
- B B B — Bin storage area
- BCP — Bin collection point
- 1.8m high brick wall with piers at 2m spacings As per Kier standard detail
- 1.8m high close board fence As per Kier standard detail
- 1.8m acoustic fence As per Kier standard detail
- 1.2m post and rail fence As per Kier standard detail
- 0.5m knee rail fence As per Kier standard detail
- 0.9m low level wall As per Kier standard detail
- Existing Metal Fence
- Gate
- Banking
- X.XX RET — Retaining wall (max. retaining as annotated)
- GB X.XX — Gravel board retaining (max. retaining as annotated)
- X.XX SOE — Slab on edge (max. retaining as annotated)

Existing post and rail fence to be relocated to extents indicated

Existing post and rail fence to be relocated to pond perimeter extents indicated

Pumping station wall to be raised to 1.8m height above highest ground level

Relocated post and rail fence to tie in with existing

Existing post and rail fence to remain

New post and rail fence to tie in with existing

REV	DESCRIPTION	DRN	CHD	DATE
C	CARPORTS REMOVED & REPLACED WITH GARAGES / PERGOLAS. POST & RAIL FENCE TO POND INDICATED	GLG	JGF	20.06.19
B	GARAGES TO PLOTS 905-912 & 930-932 CHANGED TO CARPORTS. PLOTS 918-919 & 932 REPOSITIONED	GLG	JGF	22.05.19
A	HEAVY DUTY CONSTRUCTION EXTENTS ADDED TO PRIVATE DRIVEWAYS	GLG	JGF	28.03.19

☐ PRELIMINARY ☐ INFORMATION ■ TENDER
☐ CONSTRUCTION ☐ AS BUILT

SCALE	1:200 @ A0	DATE	MARCH 2019
DRAWN	WFN	CHK	JGF
DRAWING NO.	18277-5-650	REV	C

TITLE: WYGATE POS, PHASE 7 SPALDING

DETAILS: EXTERNAL WORKS

Woods Hardwick
Architecture | Engineering | Planning | Surveying

BEDFORD : HEAD OFFICE
15-17 Goldington Road
Bedford MK40 3NH
T: +44 (0) 1234 268862

BIRMINGHAM
Fort Dunlop, Fort Parkway
Birmingham B24 9FE
T: +44 (0) 121 6297784

ONLINE: mail@woodshardwick.com | woodshardwick.com

PLEASE CONSIDER THE ENVIRONMENT BEFORE PRINTING THIS DRAWING