)SSING TO INCORPORATE
PAVING

)le Activity
)rvey undertaken 31/7/01
Ecological Services Ltd)

) Marker Posts to deliniate
Boundary

)F EMBANKMENT
OF 1 IN 2

) roads and
o properties

Council

signs

Signing and Bollard
Units by Simmonsigns

BASE LIT
KEEP LEFT/ KKEP RIGHT BOLLARD
Diag. 610 Base Lit Illuminated
Required at build out island.
450 min.clearance to kerb.

(800mm)

Priority over
oncoming
vehicles

DIAG 811.1 (50mm'X'height)
Externally Illuminated

and Bollard
Simmonsigns

DIAG 615
(75mm high)

ive way to
oncoming
vehicles

DIAG 615.1
(75mm'X'height)
nally Illuminated.

ROAD 1

SW19
SW22A
SW22B
SW22C
SW22D

Proposed build out island
as traffic calming measure
to Wygate Distributor Road
(see drawing E1350/9 for details)

1.8m verge
1.8m footway
low point
ch.189.858m

ROAD 1
CH. 234.848m
CUT LINE

Public
Open
Space

90 FVL

10m Tree Planting

Backfill ditch under roads:
Type 1 Backfill or,
similar approved material

Piped ditch to be
backfilled with
suitable material

HW21 For headwall detail,
see drawing E1350/10

108 B 4/3c B1

109 B 6/3c RS2

115 B 6/3c RS5

106 B 6/3c RS1

Pennygate Drain Improvements
detailed on drawing E1350/8

Ditch to be deepened and widened
on Western Bank, see detail drg.E1350/

HW22 For headwall detail,
see drawing E1350/10

1500mm Polelar pipe

This side of drain
9 metre byelaw

WELLAND & DEEPINGS
I.D.B.
3rd AUG 2004