BROLAC

trade colour guide

A comprehensive guide to colour choice for all Brolac Paints

BROLAC

THE PAINT FOR PROFESSIONALS

BROLAC TINTS

The Brolac Tinting facility provides an extensive choice of colours in BS 4800, RAL paint shades and unique shades, providing the professional with an extensive choice of colour.

These shades are available in each of the standard finishes. In addition, tints of Flat Oil, Superflat, Water Based Gloss and Water Based Eggshell are available from a smaller colour selection.

STRONG AND DEEP TONE COLOURS IN THE BS 4800 RANGE

Whilst most colours in the BS 4800 range cover satisfactorily, some finishing colours have less covering power than others. A different application system is recommended for these colours, as detailed below.

Brolac Full Gloss
Where indicated G apply two coats of Brolac Full Gloss over the appropriate undercoat.

Brolac PEP Vinyl Matt and Vinyl Silk Emulsions
Where indicated MS apply a base coat of Brolac PEP Vinyl Matt Emulsion Peach (06 C 33) followed by two coats of the finish.

Brolac Eggshell Low Odour
Brolac Eggshell Low Odour is a coat-on-coat system and normally two coats are satisfactory. However, where indicated LE a first coat of undercoat (as nominated for Gloss) is recommended, followed by two coats of the Eggshell Low Odour finish. Where a solvent based product is used for interior large surface applications, adequate ventilation or air fed respiratory protection equipment must be provided.

CROWN BERGER PROFESSIONAL ADVISORY SERVICE

The Crown Berger Professional Advisory Service is renowned in the trade for excellence. Expert colour and technical advice is available free of charge to trade users and specifiers of Brolac paint products.

This includes:

COLOUR ADVICE

The service will advise on any aspect of colour use and can prepare complete colour schemes from plans, drawings photographs or site visits.
The scheme is professionally presented and includes drawings and colour chips along with any specification information required.

TECHNICAL ADVICE

A team of regionally-based consultants gives advice on any aspect of specification. The service is available to anyone who requires expert advice on surface treatments, specification and the correct use of Brolac paints.

HEALTH AND SAFETY

Before storing or using any Brolac decorative products refer to the Safety Data Sheet provided by Crown Berger Limited. If for any reason this information is not available, it can be obtained from the Crown Berger Technical Advice Centre on the number below or from any Crown Brolac Decorator Centre.

Brolac products are intended for the decoration and protection of interior and exterior surfaces of buildings. Application by brush, roller, conventional and airless spray only as recommended on container. Suitability for other uses should be referred to the Crown Berger Technical Advice Centre.

Brolac decorative products are formulated to be safe and without risk to health provided they are used in accordance with the instructions for use and that common sense standards of personal hygiene and working methods are observed. Some special products require additional precautions in their use.

Who to contact:

If you need any advice on colour, technical details, or health and safety, please contact The Technical Advice Centre on:

(01254) 704951

YOUNG DECORATOR OF THE YEAR

IN ASSOCIATION WITH

PAINTING & CRAFT TEACHERS ASSOCIATIONS

Brolac are proud to confirm their continuing support for young decorators.

The 'Brolac Young Decorator of the Year' Competition seeks to find the best young decorator in the United Kingdom, and all NVQ Level II and Level III students are elligible to enter.

Brolac are keen to help maintain high standards within the profession and our support for this competition is just part of that commitment. The students of today are tomorrow's professional decorators, and Brolac products are formulated for the professional. Support and encouragement for today's students will ensure that the standards are maintained.

The Brolac 'Young Decorator of the Year' Competition is a real test of decorating skills. If you are an employer or a teacher, give your young decorators the opportunity to gain a title which will give them a real step up on the ladder of success.

YOUNG DECORATOR OF THE YEAR 1996

Competition in association with PCTA

BROLAC

UNDERCOAT

Description
- Top quality Undercoat
- Excellent coverage properties
- Ideal base for Brolac Full Gloss

Usage / Purpose
- Interior and Exterior use



Application:
- Brush, roller, conventional and airless spray

Spreading Rate:
- 14-15m² per litre

Re-Coat Time:
- 16 hours

FULL GLOSS

Description
- Exceptionally hardwearing gloss finish
- Excellent flow and film build characteristics
- Maximum colour retention

Usage / Purpose
- Interior and Exterior use
- For all domestic, commercial and industrial work



Application:
- Brush, roller, conventional and airless spray

Spreading Rate:
- 15-16m² per litre

Re-Coat Time:
- 16 hours

LOW ODOUR EGGSHELL

Description
- Premium quality durable Eggshell finish
- Resistant to steam and condensation
- Excellent flow and film build
- Low odour / Satin smooth finish

Usage / Purpose
- Interior walls and ceilings (and woodwork)
- Hardwearing finish suitable for high traffic areas



Application:
- Brush, roller, conventional and airless spray

Spreading Rate:
- 15-16m² per litre

Re-Coat Time:
- 16 hours

FLAT OIL FINISH

Description
- Matt finish - with oil based advantages - washable
- Extremely resilient and hard-wearing
- Excellent flow, film build and coverage

Usage / Purpose
- Interior walls and ceilings
- For high traffic areas



Application:
- Brush, roller, conventional and airless spray

Spreading Rate:
- 15-16m² per litre

Re-Coat Time:
- 16 hours

PEP MATT EMULSION

Description
- Premium quality emulsion - low spatter formula
- Excellent opacity
- Tough, hardwearing finish
- Good colour retention

Usage / Purpose
- For interior walls and ceilings



Application:
- Brush, roller, conventional and airless spray

Spreading Rate:
- 14-16m² per litre

Re-Coat Time:
- 4 hours

PEP SILK EMULSION

Description
- Top quality decorative finish - with low spatter formula
- Tough, washable, dirt-resistant finish
- Quick drying and low odour

Usage / Purpose
- For interior walls and ceilings where easy cleaning properties are required
- Particularly suitable for bathrooms and kitchens



Application:
- Brush, roller, conventional and airless spray
- Do not apply to surfaces that may contain moisture

Spreading Rate:
- 14-16m² per litre

Re-Coat Time:
- 4 hours

SUPERFLAT EMULSION

Description
- Emulsion formulated for new plaster & new building work
- Allows surface to breathe and dry out
- Excellent opacity
- Quick Drying

Usage / Purpose
- Interior walls and ceilings
- First time decoration to plaster, brickwork or building blocks



Application:
- Brush, roller, conventional and airless spray

Spreading Rate:
- 14-18m² per litre

Re-Coat Time:
- 4 hours

CONTRACT EMULSIONS

Description
- High Opacity Matt allows surface to breathe
- Contract Silk for washable sheen finish
- Quick Drying

Usage / Purpose
- Interior walls and ceilings
- Suitable for interior contract work



Application:
- Brush, roller, conventional and airless spray

Spreading Rate:
- 12-13m² per litre

Re-Coat Time:
- 4 hours

WEATHER COAT NO 1 FINELY TEXTURED

Description
- High quality, tough, durable Masonry Paint
- Exceptional opacity and high film build
- Flexible - covers hairline cracks
- BBA 10 year certification
- Contains an effective fungicide



Usage / Purpose
- Exterior masonry

Application:
- Brush, roller or conventional spray with stainless steel inset

Spreading Rate:
- Up to 6.5m² per litre - depending on surface roughness and porosity

Re-Coat Time:
- 4 hours

WEATHER COAT NO 2 SMOOTH

Description
- Smooth, hard-wearing masonry coating
- Contains tough, flexible resin and built in fungicide
- Excellent opacity and high spreading rate
- Dirt Resistant
- BBA 10 year certification



Usage / Purpose
- Exterior masonry

Application:
- Brush, roller, conventional and airless spray

Spreading Rate:
- Up to 10m² per litre - depending on surface roughness and porosity

Re-Coat Time:
- 4 hours

WEATHER COAT NO 3 *PLIOLITE RESIN BASED

Description
- Tough, durable, protective, year round application
- Dries in sub-zero temperatures
- Rain resistant after 15 minutes
- Requires no separate surface sealer
- BBA 10 year certification



Usage / Purpose
- Exterior masonry
- Year round use

Application:
- Brush, roller, conventional and airless spray

Spreading Rate:
- Up to 6.5m² per litre - depending on surface roughness and porosity

Re-Coat Time:
- 16 hours

*Trademark - The Goodyear Tyre and Rubber Company, Akron, Ohio, USA.

WEATHER COAT WOOD PAINT SHEEN

Description
- Attractive opaque sheen finish
- Resistant to cracking and flaking
- Self priming - no undercoat required
- Contains an effective fungicide
- Moisture-vapour permeable formulation
- BBA 5 year certification



Usage / Purpose
- Exterior use
- For joinery such as windows, door frames, doors and cladding

Application:
- Brush

Spreading Rate:
- 12m² per litre

Re-Coat Time:
- 16 hours

WATER BASED GLOSS SYSTEM

Description
- Extra-lasting acrylic alternative to oil-based gloss
- Exceptionally hardwearing microporous finish
- Enhanced film flexibility
- Prolonged retention of gloss and colour
- Fast drying

Usage / Purpose
- Interior and Exterior use



Application:
- Brush, roller

Spreading Rate:
- 10-14m² per litre

Re-Coat Time:
- 6 hours, in good drying conditions

WATER BASED EGGSHELL

Description
- Extremely durable acrylic alternative to oil-based Eggshell
- Longer life flexible film
- Prolonged colour retention
- Fast-drying
- Safer: Water based, minimal odour

Usage / Purpose
- Interior use



Application:
- Brush, roller, and airless spray

Spreading Rate:
- 12m² per litre

Re-Coat Time:
- 4 hours

VARNISHES

Description
- 4 high quality, clear protective coatings
- Excellent durability
- Tough and flexible film
- Enhances natural grain of wood

Usage / Purpose
- Hardwoods and softwoods
- Interior use - Matt, High Gloss and Eggshell
- Exterior use - Yacht and High Gloss



Application:
- Brush and conventional spray

Spreading Rate:
- 15m² per litre

Re-Coat Time:
- 16 hours

COLORTEX

Description
- High build textured wall finish
- One coat direct application - variety of colours
- Excellent durability, adhesion and flexibility
- Built-in fungicide
- BBA 10 year certification



Usage / Purpose
- Interior and exterior surfaces
- Peelable backing paper option - for future removal

Application:
- Colortex brush plus texturing rollers*

Spreading Rate:
- Up to 1.5m² per 10 litre tub - depending on surface roughness and porosity

Re-Coat Time:
- 24 hours hard dry time

*See product literature available from your supplier for more details on application.

BS 4800 INDEX

COLOUR CHIP COLUMN REFERENCE		
BS No.	Colour	
00 A 01	Oyster Grey	C
00 A 05	Sea Mist	C
00 A 09	Squirrel Grey	C
00 A 13	Nubian	C
00 E 53	Jet Black	C
00 E 55	White	
02 C 33	Wild Rose	A
02 C 37	French Violet	A
02 C 39	Ruby	C
02 C 40	Deep Plum	C
04 B 15	Malaga	A
04 B 17	Tamarisk	C
04 B 21	Pink Beige	C
04 C 33	Parisian Pink	A
04 C 37	Cameo	A
04 C 39	Burnt Rose	A
04 D 44	Kiln	A
04 D 45	Matador	A
04 E 49	Cyclamen	A
04 E 51	Coralline	A
04 E 53	Carnival Red	A
06 C 33	Peach	A
06 C 37	Bambi	A
06 C 39	Tobacco Brown	C
06 D 43	Kalahari	A
06 D 45	Andorra	A
06 E 50	Mango	A
06 E 51	Nasturtium	A
06 E 56	Adobe	A
08 B 15	Magnolia	A
08 B 17	Fawn	C
08 B 21	Pink Sand	A
08 B 25	Walnut	C
08 B 29	Bitter Chocolate	C
08 C 31	Blush Stone	A
08 C 35	Butterscotch	A
08 C 37	Ginger	A
08 C 39	Sudan	C
08 E 51	Golden Amber	A
10 A 03	Silk Grey	C
10 A 07	Russian Grey	C
10 A 11	Charcoal Grey	C
10 B 15	Milk White	A
10 B 17	Vellum	C
10 B 21	Lava	C
10 B 25	Orpheus	C
10 B 29	Amazon	C
10 C 31	Honeysuckle	A
10 C 33	Damascus	A
10 C 35	Topaz	A

COLOUR CHIP COLUMN REFERENCE		
BS No.	Colour	
10 C 39	Saluki	C
10 D 43	Banana	A
10 D 45	Olive	A
10 E 49	Pale Lemon	A
10 E 50	Druid	A
10 E 53	Canary	A
12 B 15	Tusk	B
12 B 17	Clifton Grey	B
12 B 21	Bodmin	C
12 B 25	Everglade	C
12 B 29	Cannon	C
12 C 33	Cocoon	B
12 C 39	Forest	B
12 D 43	Sapling	B
12 D 45	Tundra	B
12 E 51	Chartreuse	B
12 E 53	Jacobite	B
14 C 31	Ice Green	B
14 C 35	Ice Plant	B
14 C 39	Holly	B
14 C 40	Myrtle	B
14 E 51	Goblin	B
14 E 53	Avarice	B
16 C 33	Lugano	B
16 C 37	Juniper Green	B
16 D 45	Deep Turquoise	B
16 E 53	Seafarer	B
18 B 17	Nimbus	B
18 B 21	Quarry	C
18 B 25	Dark Admiralty Grey	C
18 B 29	Blue Grey	C
18 C 31	Snow Goose	B
18 C 35	Ontario	B
18 C 39	Deep River	B
18 D 43	Prism	B
18 E 49	Astral Blue	B
18 E 50	Ice Cap	B
18 E 51	Mermaid	B
18 E 53	Cobalt Blue	B
20 C 33	New Blue	B
20 C 37	Sea Shanty	B
20 C 40	Basun	B
20 D 45	Maritime	B
20 E 51	High Summer	B
22 B 15	Dolomite	B
22 B 17	Lilac Hint	C
22 C 37	Jupiter	C
22 D 45	Violet	C
24 C 33	Thrift	C
24 C 39	Tropic Night	C

This table identifies the full range of BS 4800 colours. The product availability index shows which products are available for each shade. Where a product is not available ready mixed, it may be supplied from the Brolac tint system.

PRIMERS, SEALERS AND SURFACE PREPARATION PRODUCTS

The Brolac primer range contains all the products needed to complement the Brolac finish range and give the best possible decorative protection on all surfaces.

	ALL PURPOSE PRIMER (BS 5358)	ALUMINIUM PRIMER	DUALCOTE ACRYLIC PRIMER/UNDERCOAT	PRIMER SEALER (ALKALI RESISTING)	WOOD PRIMER PINK & WHITE (BS 5358)	ACRYLIC WOOD PRIMER (BS 5082)	HIGH BUILD ZINC PHOSPHATE PRIMER
SURFACE							
GALVANISED IRON & STEEL	●						●
IRON & STEEL	●						●
ALUMINIUM, ALUMINIUM ALLOYS							●
SOFTWOODS		●	●		○		●
HARDWOODS		●	●		○	●	●
VERY RESINOUS SOFTWOODS						●	
DRY PLASTERS, DRY RENDERINGS etc				●			●
GLASS FIBRE, HARDBOARDS etc							●
POROUS OR POWDERY SURFACES				●			
AVAILABILITY							
5 litre	●	●	●	●	●		●
2.5 litre			●	●	●	●	●
1 litre		●	●	●			●

KEY: ● Recommended usage - see packs for detailed information.
● If used over Mordant Solution or if the surface is well weathered.
○ Interior only.

ALSO AVAILABLE:	5 litre
BITUMINOUS BASED SEALER (for use with Weather Coat No1 and No2)	●
FUNGICIDAL SOLUTION	●
STABILISING SOLUTION	●